

Submittal Data: MFZ-KX15NL

Job Name:		Location:	
Purchaser:		Submitted By:	
Submitted To:		Engineer:	
Date:		Application:	

☐ Reference

☐ Approval

☐ Construction



Basic product info.

IDU Model Number	MFZ-KX15NL	
------------------	------------	--

Electrical

Rated Voltage (Min)	208	
Recommended Fuse/Breaker Size	20	
Voltage: Indoor - Outdoor, S1-S2	208/230	
IDU Minimum Circuit Ampacity (MCA)	1	
Rated Voltage	208 / 230	

Indoor Unit

IDU Unit Dimension W (inch)	29 1/2	
IDU Unit Dimension D (inch)	8 7/16	
IDU Unit Dimension H (inch)	23 5/8	
IDU Unit Weight (lbs)	33	
IDU Airflow Rate, Cooling (Dry) CFM	198, 254, 311, 392, 431	
IDU Airflow Rate, Heating CFM	212, 268, 328, 399, 470	

Piping

IDU Liquid Pipe Size O.D. [Flared]	1/4	
IDU Gas Pipe Size O.D. [Flared]	1/2	

Refrigerant

Refrigerant Type	R454B	
------------------	-------	--

Accessories

Wall Mount controller	PAR-42MAACAB (Requires system control interface)	
Simple Wall MA Controller	PAC-YT53CRAU-J	
Simple CN105 Controller	PAC-SDW01RC-CA1	
System Interface (Full Control)	MAC-334IF-E	
System Interface (Functional Control)	MAC-497IF-E	
Remote Controller English	MAC-FL116M-E	
Remote Controller French	MAC-FL216M-E	
NA T-STAT Interface	RMF-CA200	
Wi-Fi Adapter	Built-in	
NOTES	MXZ & PUMY Branch Box Compatable	

AHRI Rated Conditions (Rated data is determined at a fixed compressor speed) (* Windscreens required for cooling operations below 23°F (-5°C))

- ¹ Cooling (Indoor // Outdoor) 80°F (26.6°C) DB, 67°F (19.4°C) WB // 95°F (35°C) DB, 75°F (23.9°C) WB
- ² Heating at 47°F (8.3°C) (Indoor // Outdoor) 70°F (21.1°C) DB, 60°F (15.6°C) WB // 47°F (8.3°C) DB, 43°F (6.1°C) WB
- ³ Heating at 17°F (-8.3°C) (Indoor // Outdoor) 70°F (21.1°C) DB, 60°F (15.6°C) WB // 17°F (-8.3°C) DB, 15°F (-9.4°C) WB
- tHeating at 5°F (-15°C) (Indoor // Outdoor) 70°F (21.1°C) DB, 60°F (15.6°C) WB // 5°F (-15°C) DB, 4°F (-15.6°C) WB
- uHeating at -4°F (-20°C) (Indoor // Outdoor) 70°F (21.1°C) DB, 60°F (15.6°C) WB // -4°F (-20°C) DB, -15°F (-26.1°C) WB

MFZ-KX15NL

Unit: inch (mm)

