


SEZ-KD09NA4R1 & SUZ-KA09NAHZ

9,000 Btu/h Horizontal Ducted Heat Pump

Job Name:	Location:	Date:
Purchaser:	Submitted by:	
Submitted to:	Reference	Approval
System Designation:	Schedule Number #:	
Engineer:		



Energy Efficiency	SEER	17.3
	EER	13.0
	HSPF	9.8

Accessories:

- Windscreens (ME-FR-24)
- External Fan/Heater Control Adapter (PAC-YU25HT-G)
- Cable Connector of Remote Sensor (PAC-SA88HA-EP)*
- *Allows control of several units with multiple remote control display

Optional Controls:

- Wireless Controller (MHK1)
- Wired Remote Controller (PAR-40MAA)
- Simple MA Remote Controller (PAC-YT53CRAU-J)
- System Control Interface (MAC-334IF-E)
- Wireless Remote (PAR-FL32MA-E) (Requires PAR-FA32MA-E)
- Remote Temperature Sensor (PAC-SE41TS-E)

Indoor unit	MCA (*)	A	1
	Fan Motor	F.L.A	0.51
	Fan Motor Output	W	96
	Air flow (Lo-Mid-Hi)	DRY(CFM)	194-247-317
		WET(CFM)	174-222-285
	External Static Pressure	in WG	0.02-0.06-0.14-0.20
	Sound Pressure Level (Lo-Mid-Hi)	dB (A)	23-26-30
	External Finish Color	Galvanized-Steel Sheets	
	Dimensions	W: in	31-1/8
		D: in	27-9/16
		H: in	7-7/8
	Weight Unit	lbs	42
	Field Drainpipe O.D.	in	O.D. 1-1/4
	Refrigerant pipe Gas	in	3/8
	Refrigerant pipe Liquid	in	1/4
	Moisture Removal	Pints/h	1.7
	Sensible Heat Factor		0.79

*All electrical work shall comply with National (CEC), local codes and regulations.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved accessories for proper functioning of the unit(s). Use of non-MESCA supported accessories will affect warranty coverage.

SEZ-KD09NA4R1 & SUZ-KA09NAHZ

Outdoor unit	MCA (*)	A	14
	MOCP (*) (Breaker)	A	24 (15)
	Fan Motor	F.L.A.	0.67
	Compressor	Model(Type)	DC INVERTER-Driven Twin Rotary
		R.L.A.	10
		L.R.A.	12.5
	Air flow (Cooling/Heating)	CFM	(1,691/1,691)
	Refrigerant Control	Linear Expansion Valve	
	Defrost Method	Reverse Cycle	
	SPL (Cooling)	dB (A)	54
	SPL (Heating)	dB (A)	55
	External Finish Color	Munsell No.3Y 7.8/1.1	
	Dimension	W: in	33-1/16
		D: in	13
H: in		34-5/8	
Weight	lbs	129	
Remote Controller	Type		Wired Remote Controller
Refrigerant	Type		R410A
	Charge	lbs, oz	3,9
	Oil	Type(Fl.oz.)	FV50S(22.0)
Refrigerant Pipe	Gas side O.D.	in	3/8
	Liquid side O.D.	in	1/4
	Height Difference (Max)	ft	40
	Length (Max.)	ft	65
Connection Method	Indoor/Outdoor		Flared/Flared
Operation Guarantee	Cooling	°F	14 - 115
	Heating	°F	- 13 - 75

Power supply	Voltage, Phase, Cycle	1-phase, 60Hz, 208/230V
Voltage	Indoor - Outdoor S1-S2	AC 208/230V
	Indoor - Outdoor S2-S3	DC12-24V
	Indoor - Remote controller	DC12V

		MAX (Btu)	MAX RATED INPUT (W)	RATED (Btu)	RATED TOTAL INPUT (W)	COP
Heating	47°F	14,098	1,332	13,250	132	3.10
	17°F	10,707	1,053	8,188	1,053	2.98
	5°F	10,707	819	5,375	819	1.92
	-4°F	7,655	626	3,216	626	1.51
	-13°F	4,604	416	797	416	0.56
Cooling	80°F	10,008	608	10,008	608	4.82

* COP at MAX capacity

NOTES : *1.Rating conditions (cooling)-Indoor : D.B. 26.7°C(80°F), W.B. 19.4°C(67°F) Outdoor : D.B. 35°C(95°F), W.B. 23.9°C(75°F)
(heating)-Indoor : D.B. 21.1°C(70°F), W.B. 15.6°C(60°F) Outdoor : D.B. 8.3°C(47°F), W.B. 6.1°C(43°F)
*2.Rating conditions(heating)-Indoor : D.B. 21.1°C(70°F), W.B. 15.6°C(60°F) Outdoor : D.B. -8.3°C(17°F), W.B. -9.4°C(15°F)

Operation range		Indoor intake air temperature	Outdoor intake air temperature
Cooling	Maximum	D.B. 35°C(95°F), W.B. 21.7°C(71°F)	D.B. 46°C(115°F)
	Minimum	D.B. 19.4°C(67°F), W.B. 13.9°C(57°F)	D.B. -10°C(14°F)
Heating	Maximum	D.B. 26.7°C(80°F), W.B. 19.4°C(67°F)	D.B. 24°C(75°F), W.B. 18°C(65°F)
	Minimum	D.B. 21.1°C(70°F), W.B. 15.6°C(60°F)	D.B. -25°C(-13°F), W.B. -26°C(-14°F)

*All electrical work shall comply with National (CEC), local codes and regulations.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved accessories for proper functioning of the unit(s). Use of non-MESCA supported accessories will affect warranty coverage.

